

Pneumatic ST-315 Fencing Stapler

Features

Proven Pneumatic Technology

- Adjustable power for high density timber
- Reliability for high volume fence construction

Aluminium Alloy Housing

- Lightweight and corrosion resistant for extreme durability

Rugged Driver Blade

- Engineered specifically for driving heavy-duty fencing staples
- Manufactured from high impact resistant steel for long life

Suitable for 1¹/₁₆" to 1¹/₂" Length Fence Batten Staples

- Ideal for rural wire and batten fencing applications

Suitable for 10¹/₂ Gauge Fence Batten Staples

Staple Wire Angle Guide

- Custom nose locates the wire for speed and reliability

Adjustable Depth of Drive

- Precision placement to prevent damage to fence wire

Top Load Magazine

- Fast reloading to minimize down-time

Adjustable Air Deflector

- Deflects discharged air away from operator for improved comfort

Sequential Trigger System

- Superior operator safety

Swivel coupling

- Greater flexibility for added convenience



Product Code	Description	Barcode
A12505	STOCK-ade Pneumatic 10 ¹ / ₂ Gauge Fence Batten Stapler	9315104016132

Pneumatic ST-315 Fencing Stapler

Specifications	A12505
Product Size (WxHxD)	14.8" x 12.2" x 3.6"
Packaged Size (WxHxD)	17.5" x 15" x 4.3"
Tool Weight	6.4lb
Packaged Weight	10.8lb
Quantity Per Pack	1
Cycle Rate	3 staples per second
Magazine Capacity	80 staples (3 strips)
Staple Range Length	1 ¹ / ₁₆ " and 1 ¹ / ₂ "
Staple Range Gauge	10 ¹ / ₂ gauge
Staple Type	Hot dipped galvanised Divergent point staple
Collation Type	Paper collated
Operating Pressure	6.2 to 8.3bar (90 to 120psi)
Optimum Operating Pressure	6.75 to 7.24bar (98 to 105psi)
Noise Level	89 to 94dB
Air Consumption at 7bar	1.1 Litres / cycle
Recommended Air Hose Fitting Diameter	³ / ₈ " to ¹ / ₂ "
Vibration Value	3.2m/s ²

Applications	
	Rural livestock fencing
	Horticulture
	Rural light mesh and light woven fencing
	Predator control fencing
	Plastic mesh, pet enclosures and poultry fencing
	Rural utilities applications
	Cladding